

Sizes & Specs - Mud-Terrain T/A® KM2

Tire Size	Service Description	Sidewall	MSPN	Rim Width Range (inches)	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth (in/32nds)	Revs/Mile at 45 mph	Max Load (lbs@psi)	Max Load Dual (lbs@psi)	Tread Pattern
LT215/75R15/C	100/97Q	RWL	12187	5.5 - 7	8.5 on 6	27.9	18	746	1765@50	1610@50	KM2
LT235/75R15/C	104/101Q	RWL	30047	6 - 7	9.3 on 6.5	29.1	18	715	1985@50	1820@50	KM2
30x9.50R15/C	104Q	RWL	06693	6.5 - 8.5	9.5 on 7.5	29.8	18	698	1985@50	N/A	KM2
31x10.50R15/C	109Q	RWL	76214	7 - 9	10.5 on 8.5	30.8	19	675	2270@50	N/A	KM2
32x11.50R15/C	113Q	RWL	33561	8 - 10	11.4 on 9	31.8	20	654	2535@50	N/A	KM2
33x10.50R15/C	114Q	RWL	19791	7 - 9	10.5 on 8.5	32.8	18	634	2600@50	N/A	KM2
33x12.50R15/C	108Q	RWL	16475	8.5 - 11	12.5 on 10	32.8	20	634	2205@35	N/A	KM2
35x12.50R15/C	113Q	RWL	44299	8.5 - 11	12.5 on 10	34.8	20	598	2535@35	N/A	KM2
LT225/75R16/D	110/107Q	RWL	10131	6 - 7	8.8 on 6	29.5	18	705	2335@65	2150@65	KM2
LT235/70R16/C	104/101Q	RWL	22805	6 - 7.5	9.5 on 7	29.2	18	712	1985@50	1820@50	KM2
LT235/85R16/E	120/116Q	RWL	43486	6 - 7.5	9.3 on 6.5	32	18	650	3042@80	2778@80	KM2
LT245/75R16/E	120/116Q	RWL	85574	6.5 - 8	9.8 on 7	30.7	18	678	3042@80	2778@80	KM2
LT255/70R16/D	115/112Q	RWL	01835	6.5 - 8	10.2 on 7.5	30.3	18	686	2680@65	2470@65	KM2
LT255/85R16/E	123/120Q	RWL	11029	6.5 - 8	10 on 7	33.3	18	625	3415@80	3085@80	KM2
LT265/75R16/E	123/120Q	RWL	33231	7 - 8	10.5 on 7.5	31.9	18	652	3415@80	3085@80	KM2
LT285/75R16/E	126/123Q	RWL	06464	7.5 - 9	11.3 on 8	33.1	19	628	3750@80	3415@80	KM2
LT305/70R16/D	118/115Q	RWL	37159	8 - 9.5	12.2 on 9	33.1	20	628	2910@50	2680@50	KM2
LT315/75R16/D	121Q	RWL	24970	8 - 10	12.3 on 8.5	34.8	20	598	3195@50	N/A	KM2
LT245/70R17/E	119/116Q	RWL	99340	6.5 - 8	9.8 on 7	30.8	18	676	3000@80	2755@80	KM2
LT285/70R17/D	121/118Q	RWL	36575	7.5 - 9	11.5 on 8.5	33	19	630	3195@65	2910@65	KM2
LT305/65R17/E	121/118Q	RWL	34424	8.5 - 11	12.2 on 9	32.8	20	634	3195@65	2910@65	KM2
35x12.50R17/D	119Q	RWL	38371	8.5 - 11	12.5 on 10	34.8	20	598	3000@50	N/A	KM2
37x12.50R17/D	124Q	RWL	02707	8.5 - 11	12.5 on 10	36.8	20	566	3525@50	N/A	KM2
38x14.50R17/D	121Q	BSW	23241	10 - 12	14.7 on 12	37.8	20	551	3195@50	N/A	KM2
40x14.50R17/C	121Q	BSW	10977	10 - 12	14.7 on 12	39.8	20	523	3195@35	N/A	KM2
LT305/60R18/E	121/118Q	RWL	31489	8.5 - 11	12.2 on 9	32.6	20	637	3195@65	2910@65	KM2
35x12.50R18/D	118Q	RWL	28459	8.5 - 11	12.5 on 10	34.8	20	598	2910@50	N/A	KM2
37x12.50R18/D	123Q	RWL	97218	8.5 - 11	12.5 on 10	36.8	20	566	3415@50	N/A	KM2
LT305/55R20/E	121/118Q	RWL	20881	8.5 - 11	12.4 on 9.5	33.5	20	622	3195@65	2910@65	KM2
LT325/60R20/D	121Q	RWL	34143	9 - 12	13 on 9.5	35.6	20	584	3195@50	N/A	KM2
37x12.50R20/D	120Q	RWL	39143	8.5 - 11	12.5 on 10	36.8	20	566	3085@50	N/A	KM2
42x14.50R20/C	125Q	BSW	96757	10 - 12	14.7 on 12	41.8	20	498	3640@35	N/A	KM2
LT335/55R22/D	121Q	BSW	10687	9 - 12	13.9 on 11	36.7	20	566	3195@50	N/A	KM2

Government UTQG Ratings do not apply to light truck sized tires.

1. The sizes shown are average design values for tires measured on specified measuring rim widths. Some tires may vary from this value by +/-3% of the section height (affecting overall diameter), and +/-4% of the section width.
2. Section width varies approximately 0.2" (5mm) for every 0.5" change in rim width.

WARNING: Serious or fatal injury may result from tire failure due to underinflation or overloading. To ensure correct air pressure and vehicle load, refer to vehicle owner's manual or tire information placard on the vehicle. Serious injury or death may result from explosion tire/rim assembly due to improper mounting. Only tire professionals should mount tires and they should never inflate beyond 40 psi to seat the beads. Before mixing types of tires in any configuration on any vehicle, be sure to check the vehicle owner's manual for its recommendations.

DANGER: Never mount a 16" diameter tire on a 16.5" rim.
DANGER: Never mount a 17" diameter tire on a 17.5" rim.

Inflation pressure increase must not exceed the maximum pressure branded on the tire sidewall. When a customer requests a replacement tire with a lower speed rating than the original equipment tire, you must clearly communicate to him or her that the handling of the vehicle may be different, and that its maximum speed capability is limited to that of the lowest speed-rated tire on the vehicle. Exceeding the lawful speed limit is neither recommended nor endorsed.